

# United States Patent [19]

[11] Patent Number:

5,811,808

[45] Date of Patent:

Sep. 22, 1998

# Cannata et al.

[54]	INFRARED IMAGING SYSTEM
	EMPLOYING ON-FOCAL PLANE
	NONUNIFORMITY CORRECTION

[75] Inventors: Robert F. Cannata. Santa Barbara. Calif.; Jeffrey L. Metschuleit.

Fisherville, Ky.

[73] Assignee: Amber Engineering, Inc., Goleta.

Calif.

[21] Appl. No.: 712,891

[56]

[22] Filed: Sep. 12, 1996

[51] Int. Cl.<sup>6</sup> ...... G01J 5/20; G01J 5/24

[52] U.S. Cl. ...... 250/332; 250/349; 250/370.08

# References Cited

#### U.S. PATENT DOCUMENTS

4,719,512		Endo et al
4,752,694 4,771,267		Hegel, Jr. et al Russell, Jr. et al
4,903,144	2/1990	Stefanik et al.
4,953,028 4,987,294		Murayama et al Romer .
5,157,500	10/1992	Gusmano.
5,159,457 5,162,912		Kawabata . Ueno et al

5,182,446	1/1993	Tew .	ဦ <u></u>	Ì
5,286,976	2/1994	Cole .	مر ر	i
5,300,915	4/1994	Higashi et al	<b>=</b> 5.	_
5,489,776	2/1996	Lung	250/332 vs 🗪 🧱	5
5,528,035	6/1996	Masarik et al	250/332	>
FO	REIGN	PATENT DOCUMENTS	9/6	70/
5-264357	10/1993	Japan	250/3320	

Primary Examiner—Edward J. Glick Attorney, Agent, or Firm—Graham & James LLP

# [57] ABSTRACT

An infrared imaging system having a focal plane array including an array of detector elements and a readout circuit and including nonuniformity correction circuitry on the focal plane array. The individual detector elements correspond to pixels of an infrared scene to be imaged. Offsets in detection signals from each pixel arising from nonuniformities in the individual detector elements in the array are corrected by storing offset correction values for each detector element and using the stored offset values to control correction circuitry as the respective detector element signals are read out. The detector array and readout circuit are preferably formed as a monolithic or hybrid structure and the offset correction is provided on the focal plane array prior to signal amplification and analog to digital conversion.

# 35 Claims, 10 Drawing Sheets

